




### Solder and Flux

Accu-Glass solder provides a clean, positive electrical connection that does not outgas. The melting/flow temperature is 280°C. It is suitable for use in ultrahigh vacuum applications. This is an 85% gold and 15% proprietary alloy.



**110796** / UHV Solder



**110800** / Soldering Iron with Interchangeable Tips



**110797** / UHV Solder Flux

### Solder and Flux — 250°C / UHV to 1x10<sup>-10</sup> Torr

Unit Quantity	Size Length / Diameter	Description	Model Number	Part Number	Unit Price \$
---------------	------------------------	-------------	--------------	-------------	---------------

### Solder and Flux — plus Butane Soldering Iron / Refills

1	1 / 0.02	Accu-Glass alloy	UHV-SOLDER	<b>110796</b>	39
1 <sup>1,2</sup>	0.5 oz	Solder flux <sup>2</sup>	S-FLUX	<b>110797</b>	45
1	—	Soldering iron, butane	S-IRON	<b>110800</b>	155
1 <sup>1</sup>	4.5 oz	Butane refill bottle	S-IBREF	<b>110804</b>	24

1. Hazardous material; cannot be shipped by air. No express or international delivery available.

2. Soluble in isopropyl alcohol. Recommended cleaning after use: 5 minutes in ultrasonic bath of isopropyl alcohol.